In re Patent Application of:

GARNIER ET AL.

Serial No. 09/499,060

Filing Date: February 4, 2000

Ford

charging current to be proportional to a square of a ratio of the second resistance and the first resistance, said first and second resistances having a same type technology.

15. (Three Times Amended) An integrated circuit voltage ramp generator produced using semiconductor technology and comprising:

a capacitance; and

a charging circuit connected to said capacitance and

a current generator having a first resistance, and

a degenerate current mirror circuit connected to said current generator and to said capacitance, said degenerate current mirror circuit having a second resistance for generating a capacitance charging current that is proportional to a square of a ratio of the second resistance and the first resistance, said first and second resistances having a same type technology.

21. (Three Times Amended) An integrated circuit current ramp generator produced using semiconductor technology and comprising:

a voltage ramp generator comprising

a capacitance, and

a charging circuit connected to said capacitance and comprising

In re Patent Application of: GARNIER ET AL.

Serial No. 09/499,060

Filing Date: February 4, 2000

a current generator having a first resistance, and

Fry

a circuit connected to said current generator and to said capacitance, said circuit having a second resistance and enabling a capacitance charging current to be proportional to a square of a ratio of the second resistance and the first resistance, said first and second resistances having a same type technology; and

a conversion circuit connected to said voltage ramp

generator for generating a current ramp.

24. (Twice Amended) An integrated circuit current ramp generator according to Claim 21, wherein said charging circuit comprises a degenerate current mirror circuit.

- 29. (Three Times Amended) An integrated circuit current ramp generator produced using semiconductor technology and comprising:
 - a voltage ramp generator comprising

 a capacitance having a first resistance, and

 a charging circuit connected to said

 capacitance and comprising
 - a current generator, and
 - a degenerate current mirror circuit connected to said current generator and to said capacitance, said degenerate current mirror circuit having a second resistance for generating a capacitance charging current that